

Certificate of Technical Specifications

portinari

ambientes com emoção

PRODUCT: SERENA HD GR HARD
FORMAT: 584,0 mm X 1170,0 mm X 9,0 mm

CONTAINS: 2 Peças 1,37 m² 14,75 SQFT

GROUP: Bla

Technical Characteristics	ISO	Req.	Unit	Specification
DIM. VAR. IN REL. W. OF THE GREATER SIDE	10545-2	±1,0	mm	±0,50
DIM. VAR. IN REL. W. OF THE MINOR SIDE	10545-2	±1,0	mm	±0,50
THICKNESS VARIATION	10545-2	±0,50	mm	±0,50
STRAIGHTNESS OF THE GREATER SIDE	10545-2	±0,80	mm	±0,80
STRAIGHTNESS OF THE MINOR SIDE	10545-2	±0,80	mm	±0,80
DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE	10545-2	±1,50	mm	±1,50
DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE	10545-2	±1,50	mm	±1,50
CENTRAL DIAGONAL CURVATURE DEVIATION	10545-2	±1,80	mm	±1,80
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±1,80	mm	±1,80
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±1,80	mm	±1,80
BENDING OVER DIAGONAL	10545-2	±1,80	mm	±1,80
QUALITY OF SURFACE	10545-2	≥95	%	≥95
WATER ABSORPTION	10545-3	≤0,50	%	≤0,50
RESISTANCE TO BENDING	10545-4	≥35	N/mm²	≥35
BREAKING STRENGTH	10545-4	≥1300	N	≥1300
CLASS OF USAGE		Especificar	USO	6
THERMAL SHOCK RESISTANCE	10545-9	-	-	-
LINEAR EXPANSION COEFFICIENT X 10-6	10545-8	-	C-1	-
MOISTURE EXPANSION	10545-10	≤0,60	mm/m	≤0,30
GRAZING RESISTANCE	10545-11	Requerida	-	OK
RESISTANCE TO CHEMICALS	10545-13	Min,Classe GB	-	GA
RESISTANCE ATTACKS ACID/ALKALINE	10545-13	Especificar	-	GLB
SURFACE RESISTANCE TO STAINS	10545-14	Min,Classe 3	-	4
COEFFICIENT OF FRICTION WET	NBR 16919	Especificar		≥0,6*
CHANGES IN HUE				V3

Note: Product in accordance with ABNT NBR 13006 standard
Reaction to fire evaluation (NBR15575): Class I (non-combustible)
Class 6: All residential and commercial areas with heavy traffic.



Andre Bez Batti
Responsável Técnico