

# Certificate of Technical Specifications

PRODUCT: WHITE PLAIN LUX BOLD  
 FORMAT: 298,0X601,0X8,5 MM CONTAINS: 12 Pieces 2,15 m2 23,14 SQFT GROUP: BIII

Technical Characteristics	ISO	Req.	Unit	Specification
DIM. VAR. IN REL. W. OF THE GREATER SIDE	10545-2	±2.0	mm	±2.0
DIM. VAR. IN REL. W. OF THE MINOR SIDE	10545-2	±1.70	mm	±1.70
THICKNESS VARIATION	10545-2	±5	%	±5
STRAIGHTNESS OF THE GREATER SIDE	10545-2	±1.50	mm	+0.90 / -0.60
STRAIGHTNESS OF THE MINOR SIDE	10545-2	±1.47	mm	+0.50 / -0.30
DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE	10545-2	±2.0	mm	±2.0
DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE	10545-2	±1.47	mm	±1.2
CENTRAL DIAGONAL CURVATURE DEVIATION	10545-2	±2.0	mm	+2.0 / -0.70
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±2.0	mm	+1.80 / -0.60
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±1.47	mm	+0.90 / -0.30
BENDING OVER DIAGONAL	10545-2	±2.0	mm	±2.0
QUALITY OF SURFACE	10545-2	≥95	%	≥95
WATER ABSORPTION	10545-3	> 10	%	> 10
RESISTANCE TO BENDING	10545-4	≥12	N/mm2	≥15
BREAKING STRENGTH	10545-4	≥600	N	≥700
CLASS OF USAGE		Specify	USO	1
THERMAL SHOCK RESISTANCE	10545-9	-	-	OK
LINEAR EXPANSION COEFFICIENT X 10-6	10545-8	-	C-1	5.8 a 7.0
MOISTURE EXPANSION	10545-10	-	mm/m	≤0.30
GRAZING RESISTANCE	10545-11	-	-	OK
RESISTANCE TO CHEMICALS	10545-13	Minimum Class GB	-	GA
RESISTANCE ATTACKS ACID/ALKALINE	10545-13	Specify	-	GLB
SURFACE RESISTANCE TO STAINS	10545-14	Minimum Class 3	-	4
COEFFICIENT OF FRICTION WET	NBR16919	Specify		-
CHANGES IN HUE				V1

Note: Product in accordance with ABNT NBR 13006 standard  
 Reaction to fire evaluation (NBR15575): Class I (non-combustible)  
 USE 1 – Use on internal walls.



Rodrigo Pereira Guedin  
Diretor Industrial