

Certificate of Technical Specifications

portinari

ambientes com emoção

PRODUCT: CHARM CUBIC GR MATTE
 FORMAT: 291.0 X 584.0mm X 9 mm CONTAINS: 8 Pieces 1,36m2 14,64 SQFT GROUP: BIII

| Technical Characteristics | ISO | Req. | Unit | Specification |
|--|----------|------------------|-------|---------------|
| DIM. VAR. IN REL. W. OF THE GREATER SIDE | 10545-2 | ±1.0 | mm | ±0.50 |
| DIM. VAR. IN REL. W. OF THE MINOR SIDE | 10545-2 | ±0.87 | mm | ±0.50 |
| THICKNESS VARIATION | 10545-2 | ±0.45 | mm | ±0.45 |
| STRAIGHTNESS OF THE GREATER SIDE | 10545-2 | ±0.80 | mm | ±0.50 |
| STRAIGHTNESS OF THE MINOR SIDE | 10545-2 | ±0.80 | mm | ±0.30 |
| DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE | 10545-2 | ±1.50 | mm | ± 0.80 |
| DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE | 10545-2 | ±0.87 | mm | ±0.60 |
| CENTRAL DIAGONAL CURVATURE DEVIATION | 10545-2 | - | - | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | - | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | - | - |
| BENDING OVER DIAGONAL | 10545-2 | - | - | - |
| QUALITY OF SURFACE | 10545-2 | ≥95 | % | ≥95 |
| WATER ABSORPTION | 10545-3 | > 10 | % | > 10 |
| RESISTANCE TO BENDING | 10545-4 | ≥12 | N/mm2 | ≥15 |
| BREAKING STRENGTH | 10545-4 | ≥600 | N | ≥600 |
| CLASS OF USAGE | 10545-7 | Specify | USE | 1 |
| THERMAL SHOCK RESISTANCE | 10545-9 | - | - | OK |
| LINEAR EXPANSION COEFFICIENT X 10-6 | 10545-8 | - | C-1 | 5.8 a 7.0 |
| MOISTURE EXPANSION | 10545-10 | - | mm/m | ≤0.30 |
| GRAZING RESISTANCE | 10545-11 | - | - | OK |
| RESISTANCE TO CHEMICALS | 10545-13 | Minimum Class GB | - | GA |
| RESISTANCE ATTACKS ACID/ALKALINE | 10545-13 | Specify | - | GLB |
| SURFACE RESISTANCE TO STAINS | 10545-14 | Minimum Class 3 | - | 4 |
| COEFFICIENT OF FRICTION WET | NBR16919 | Specify | - | - |
| CHANGES IN HUE | | | | V2 |

Note: Product in accordance with ABNT NBR 13006 standard
 Reaction to fire evaluation (NBR15575): Class I (non-combustible)
 USE 1- Use on internal walls.



Rodrigo Pereira Guedin
 Diretor Industrial