

Certificate of Technical Specifications

PRODUCT: MAX ABSTRACT WH NAT
 FORMAT: 201.3 X 201.3mm X 11.0 mm CONTAINS: 4 Piece 0,16 m2 1,72 SQFT GROUP: Bla

Technical Characteristics	ISO	Req.	Unit	Specification
DIM. VAR. IN REL. W. OF THE GREATER SIDE	10545-2	±0.60	mm	±0.50
DIM. VAR. IN REL. W. OF THE MINOR SIDE	10545-2	±0.60	mm	±0.50
THICKNESS VARIATION	10545-2	±0.5	mm	±0.50
STRAIGHTNESS OF THE GREATER SIDE	10545-2	±0.60	mm	±0.60
STRAIGHTNESS OF THE MINOR SIDE	10545-2	±0.60	mm	±0.60
DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE	10545-2	±0.60	mm	±0.50
DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE	10545-2	±0.60	mm	±0.50
CENTRAL DIAGONAL CURVATURE DEVIATION	10545-2	-	mm	-
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	-	mm	-
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	-	mm	-
BENDING OVER DIAGONAL	10545-2	-	mm	-
QUALITY OF SURFACE	10545-2	≥95	%	≥95
WATER ABSORPTION	10545-3	≤0.5	%	≤0.5
RESISTANCE TO BENDING	10545-4	≥35	N/mm2	≥35
BREAKING STRENGTH	10545-4	≥1300	N	≥1700
CLASS OF USAGE			USO	2
THERMAL SHOCK RESISTANCE	10545-9	-	-	OK
LINEAR EXPANSION COEFFICIENT X 10-6	10545-8	-	°C-1	-
MOISTURE EXPANSION	10545-10	-	mm/m	≤0.30
GRAZING RESISTANCE	10545-11	-	-	OK
RESISTANCE TO CHEMICALS	10545-13	Minimum Class GB	-	GA
RESISTANCE ATTACKS ACID/ALKALINE	10545-13	Specify	-	GLB
SURFACE RESISTANCE TO STAINS	10545-14	Minimum Class 3	-	4
COEFFICIENT OF FRICTION WET	NBR16919	Specify		-
CHANGES IN HUE				V2

Note: Product in accordance with ABNT NBR 13006 standard
 Reaction to fire evaluation (NBR15575): Class 1 (non-combustible)
 USE 2 - Use on internal and external walls.



Rodrigo Pereira Guedin
Diretor Industrial