


Certificate of Technical Specifications

PRODUCT: MEZZO DECOR MAX BE ETR
 FORMAT: 500,0X1200,0X25 MM CONTAINS: CC GROUP: Bla

| Technical Characteristics | ISO | Req. | Unit | Specification |
|--|----------|------------------|-------------------|---------------|
| DIM. VAR. IN REL. W. OF THE GREATER SIDE | 10545-2 | - | mm | - |
| DIM. VAR. IN REL. W. OF THE MINOR SIDE | 10545-2 | - | mm | - |
| THICKNESS VARIATION | 10545-2 | - | mm | - |
| STRAIGHTNESS OF THE GREATER SIDE | 10545-2 | - | mm | - |
| STRAIGHTNESS OF THE MINOR SIDE | 10545-2 | - | mm | - |
| DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE | 10545-2 | - | mm | - |
| DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE | 10545-2 | - | mm | - |
| CENTRAL DIAGONAL CURVATURE DEVIATION | 10545-2 | - | mm | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | mm | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | mm | - |
| BENDING OVER DIAGONAL | 10545-2 | - | mm | - |
| QUALITY OF SURFACE | 10545-2 | - | % | - |
| WATER ABSORPTION | 10545-3 | - | % | - |
| RESISTANCE TO BENDING | 10545-4 | - | N/mm ² | - |
| BREAKING STRENGTH | 10545-4 | - | N | - |
| CLASS OF USAGE | | Specify | Use | 2 |
| THERMAL SHOCK RESISTANCE | 10545-9 | - | - | - |
| LINEAR EXPANSION COEFFICIENT X 10-6 | 10545-8 | - | °C-1 | - |
| MOISTURE EXPANSION | 10545-10 | - | mm/m | - |
| GRAZING RESISTANCE | 10545-11 | - | - | - |
| RESISTANCE TO CHEMICALS | 10545-13 | Minimum Class GB | - | - |
| RESISTANCE ATTACKS ACID/ALKALINE | 10545-13 | Specify | - | - |
| SURFACE RESISTANCE TO STAINS | 10545-14 | Minimum Class 3 | - | - |
| COEFFICIENT OF FRICTION WET | NBR16919 | Specify | | - |
| CHANGES IN HUE | | | | V3 |

Note: Product in accordance with ABNT NBR 13006 standard
 Reaction to fire evaluation (NBR15575): Class I (non-combustible)
 USE 2 - Use on internal and external walls.


 Andre Bez Batti
 Responsável Técnico